



Smooth Top Square Edge Stair Coping 12x12, Heavy Sandblast, Meadow Green, Shopping Center, Palos Verdes, CA

### Smooth Top Square Edge Stair Coping 12"x 14"x 2"x 34"

PO Box 5565 Compton, CA 90224 310-639-8960

### **Product Type:**

Paver Tile Trim/Accessory

### Recommended Use:

Exterior, Interior, Residential, Commercial Pedestrian, Light Vehicular, Floor or Wall Veneer

### **Installation:**

Mortar (aka wet) Set, Thin Set (CTMA method)

### Packaging Type:

Check with the factory for details.

### Available Finishes:

Smooth, Light, Medium, Heavy Sandblast, Polished

# Stair Coping 14" deep



## <u>Design Style:</u>

Contemporary Mid Century

**Smooth Troweled Concrete** 

### **Complementary Paver Tiles:**

6x6, 6x12, 18x18, 24x24 and many more. Contact the factory for details.

### Matching Accessory / Trim Units::

Surface Bullnose, Riser, Cove Base

### Color Selection:

Select colors from the current Cal-Ga-Crete or Davis Colors chart.

Test Results:	ASTM #	<u>Results</u>	Comments
Water Absorption	C-373	7.75%	Unsealed
Breaking Strength	C-648	988 lbs	0.75" thickness
Modulus of Rupture	C-674	1374	0.75" thickness
Abrasive Hardness	C-501	27	
Coefficient of Friction (COF)	C-1028-07	0.70	Smooth Surface
Coefficient of Friction (COF)	C-1028-07	0.77	Light Sandblast
Compressive Strength	C-140-75	6027	0.825" thickness

#### Notes:

Expect naturally occurring color variations typical for concrete, unglazed ceramic and stone tile products. Apply a quality sealer for wear factor improvement and ease of maintenance. Notify the factory in case of intended exterior use in freeze-thaw climates.

#### **Technical and Contact Information:**

Review the latest care and installation recommendations available on Cal-Ga-Crete's website www.calgacrete.com. For inquiries email info@calgacrete.com or call 310-639-8960.