



TumbleStone 4x4, Mixed Colors, Hotel Restaurant, Las Vegas, NV



## TumbleStone 4" x 4" x 3%"

PO Box 5565 Compton, CA 90224 310-639-8960

4"

**Design Style:** 

Antique Marble Worn Stone Tile

**Tumbled Marble** 

4"

**Product Type:** 

Paver Tile

Recommended Use:

Exterior, Interior, Residential, Commercial Pedestrian, Light Vehicular, Floor or Wall Veneer

**Installation:** 

Mortar (aka wet) Set, Thin Set (CTMA method)

Packaging / Weight:

Boxed (25 pcs), Pallets (24 boxes), 8 lbs per sq ft

**Suggested Finishes:** 

Natural. Light, Medium or Heavy Sandblast.

**Complementary Paver Tiles:** 

Tumblestone 12x12

Matching Accessory / Trim Units::

Surface Bullnose 12x12

Color Selection:

Select colors from the current Cal-Ga-Crete or Davis Colors chart.

| Test Results:                 | ASTM #    | <u>Results</u> | <b>Comments</b>  |
|-------------------------------|-----------|----------------|------------------|
| Water Absorption              | C-373     | 7.75%          | Unsealed         |
| Breaking Strength             | C-648     | 988 lbs        | 0.75" thickness  |
| Modulus of Rupture            | C-674     | 1374           | 0.75" thickness  |
| Abrasive Hardness             | C-501     | 27             |                  |
| Coefficient of Friction (COF) | C-1028-07 | 0.70           | Smooth Surface   |
| Coefficient of Friction (COF) | C-1028-07 | 0.77           | Light Sandblast  |
| Compressive Strength          | C-140-75  | 6027           | 0.825" thickness |

## Notes:

Expect naturally occurring color variations typical for concrete, unglazed ceramic and stone tile products. Apply a quality sealer for wear factor improvement and ease of maintenance. Notify the factory in case of intended exterior use in freeze-thaw climates.

## Technical and Contact Information:

Review the latest care and installation recommendations available on Cal-Ga-Crete's website www.calgacrete.com. For inquiries email info@calgacrete.com or call 310-639-8960.